

## **Key Features & Benefits**

weldmax |

- Horizontal load 100kg
- Vertical load 50kg
- Rotation speed 0.5-5 rpm
- Tilting range 0- 90 deg
- Table Dia 400mm
- Table center hole 45mm







PT 300



PT 600

	PT 100	PT 300	PT 600	PT 1200
Horizontal Load	100 KG	300kg	600kg	1200kg
Vertical Load	50 KG	150kg	300kg	600kg
Rotation Speed (RPM)	0.50-5.0	0.25-2.5	0.10-1.0	0.12-1.2
Tilting Range	90°	90°	90°	90°
Tilting Diameter	400mm	500mm	600mm	90
Table Centre hole	45mm	90mm	Nil	1200mm
Voltage	240V	240V	415V	Nil
Hertz	50Hz	50Hz	50Hz	50Hz
Phase	1	1	3	3
Tilting adjustment	Manual	Manual	Electric	Electric
Table Height (Horizontal)	503mm	602mm	755mm	910mm
MADE IN ITALY		U		

- Easy to set up a small welding center equipped with quick chuck, torch holder and roller supports.
- DC infinitely variable speed control system.
- Time relay is equipped for auto welding.
- High frequency protection on electric box.
- Compact and robust design, easy to operate.



## **Ancillary Items**



**160MM 3 JAW CHUCK** K11-160



**200 MM 3 JAW CHUCK** K11-200



**200 MM 3 JAW CHUCK** K11-250



PIPE STAND 1135KG
FOLDING LEG STAINLESS
V-HEAD JACK
WMXPSV




BTA ball transfer head



BD-L LINEAR WELDING OSCILLATOR UNIT ED-WLS



TORCH HOLDER 1000H X 400W TH350



3WAY TORCH ADJUSTOR SLIDE W/TCH ANGLE WCS-222

